

FX Australia® Product Information

FX Cable Black

Product Description

FX Cable Black is a flat, non-reflective, hard-wearing 100% acrylic paint, specifically formulated for hiding imperfections in interior ceilings and is also used for coating wooden cable reels.

Features

Water-based
High opacity

Benefits

2-hour recoat
Easy clean-up

Uses

FX Cable Black is used for unpainted and previously painted wooden cable reels and imperfect/unusual ceilings.

Colours: Standard black. FX Australia can custom-tint product to meet individual requirements.

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint. Flatten gloss surfaces by thoroughly sanding. Wipe clean with a damp cloth. Some unpainted/painted substrates may require undercoating prior to using FX Cable Black depending on condition/type of substrate. Call FX Australia for more details.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action.

Brush/Roller: Apply using a 75 mm brush, or a 20 mm nap roller.

Airless/Conventional Spray: Suitable for application using all standard spray equipment.

Approximate Spreading Rate: 8–12 square metres per litre on unpainted surfaces and up to 16 square metres per litre on previously painted surfaces, depending on application technique and surface roughness.

Requires: 1–2 coats.

Thinner: Water, up to 10% if required.

Tinting: N/A.

Method: Brush, roller or airless/conventional spray equipment.

Shelf Life: 12 months.

Drying Times (at 25 °C): Touch: 2 Hours; **Recoat:** 4 Hours

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.

The temperature should not fall below 10 °C during the drying process.

Clean-up: Water. **Safety:** Dust Mask. **Gloss level:** Less than 5% at a 60° viewing angle.

Safety and Environmental Care

Safety

Personal Protection: Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation.

Asbestos cement sheeting: Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite or other inert material • Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.

Date of Issue: March 2014