

FX Australia® Product Information

FX Lemon Tree Creek® Ceiling Flat (Interior only)

Product Description

FX Lemon Tree Creek® Ceiling Flat is a high-performance, hard-wearing interior and exterior acrylic coating specifically formulated for use in all domestic and commercial situations where environmental safety and peace of mind are paramount. It incorporates advanced molecular sieve technology to absorb odours and toxins, is APEO-free* and VOC-free** and is developed for ease of application and superior durability. **This product is part of the FX Lemon Tree Creek® integrated system of ultra-safe paints and used with FX Lemon Tree Creek® Sealer Undercoat, gives a perfect finish on ceilings.**

Features

Water-based
Molecular Sieve Technology
APEO-free*
VOC-free**

Benefits

Ease of application
Easy spreading
Excellent opacity
Easy clean-up
Safeguarding your environment

Uses

FX Lemon Tree Creek® Ceiling Flat is ideal for sealed interior surfaces, such as plaster, plasterboard and cement render. **It is also suitable for sheltered exterior surfaces, such as eaves.**

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces, by thoroughly sanding and wipe clean with a damp cloth. Then apply FX Lemon Tree Creek® Sealer Undercoat as required.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action.

Brush/Roller: Apply product with a 75 mm–100 mm brush, or using a medium or long nap roller.

Airless/Conventional Spray: Suitable for application using all standard spray equipment. Up to 10% water per litre may be added to aid atomisation.

Approximate Spreading Rate: 13 square metres per litre depending on application technique and surface roughness.

Approximate Film Thickness per coat: Wet: 90 Microns; **Dry:** 25 Microns.

Requires: 2 coats.

Thinner: If required, add up to 100 ml of water per litre to assist in application.

Tinting: Refer to colour chart for tinting specifications.

Method: Brush, roller or airless/conventional spray equipment.

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.

The temperature should not fall below 10 °C during the drying process.

Drying Times (at 25 °C): Touch: 30 Minutes; **Recoat:** 4 Hours.

Clean up: Water. **Safety:** Dust Mask. **Gloss Level:** Less than 5% at a 60° viewing angle.

*APEO-free: APEOs (Alkylphenol ethoxylates) are non-ionic surfactants with an emulsifying and dispersing action, known for their poor biodegradability and toxicity, especially to marine life.

**VOC-free: VOCs (Volatile Organic Compounds) are chemical compounds that vaporise and enter the air, contributing to inside and outside air pollution.

Safety and Environmental Care

Safety

Personal Protection: Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation.

Asbestos cement sheeting: Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite or other inert material • Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.

Date of Issue: March 2014