

FX Australia® Product Information

FX MAX Solar Low Sheen, Semi-Gloss or Gloss (Interior & Exterior)

Product Description

FX MAX Solar Low Sheen, Semi-Gloss or Gloss is a high-performance, washable 100% acrylic coating for interior and exterior walls. It guarantees long-term protection against the extremes of Australian weather so will not blister, peel or flake even in the harshest sun, wind or snow, and is specifically formulated to minimise the time and work required for maximum results.

Features

Water-based
Washable
Tintable

Benefits

Ease of application
Easy spreading
Easy clean-up

Uses

FX MAX Solar Low Sheen, Semi-Gloss or Gloss is ideal for interior and exterior surfaces such as plaster, plasterboard, timber, iron and cement render.

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply FX MAX Solar Superprep as required, one coat minimum.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action.

Brush/Roller: Apply product using a 75 mm–100 mm brush, or medium or long nap roller.

Airless/Conventional spray: Suitable for application using all standard equipment. Up to 10% water may be added to aid atomisation.

Approximate Spreading Rate: 14–16 square metres per litre, depending on application technique and surface roughness.

Approximate Film Thickness per coat: Wet: 100 Microns; **Dry:** 30 Microns.

Requires: 2 coats.

Thinner: Water, 10% if required.

Tinting: Refer to colour chart for tinting specifications.

Method: Brush, roller, airless/conventional spray equipment.

Drying Times (at 25 °C): Touch: 40 Minutes; **Recoat:** 3 Hours.

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.

The temperature should not fall below 10 °C during the drying process.

Clean-up: Water. **Safety:** Dust Mask. **Gloss Level:** 5%–10% at a 60° viewing angle.

Safety and Environmental Care

Safety

Personal Protection: Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation.

Asbestos cement sheeting: Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite or other inert material • Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.

VOC Content: Less than 19 grams per litre

Date of Issue: March 2014