



FX Australia® Product Information

FX Clear (Interior only)

Product Description

FX Clear is a hardwearing, washable liquid paste that dries to a satin finish, and is specifically formulated for producing unusual and creative finishes. It is custom-tintable, can be used on its own or with other FX products, such as FX French Wash, and untinted, acts as a protective coating in high traffic areas. **This is a specialty product. The end-result may differ from the FX Standard or images on social media depending on applicator technique and expertise. Always test the product before commencing a project.**

Features

Water-based
Attractive finish
Washable
Tintable

Benefits

Ease of application
Easy spreading
Easy clean-up

Uses

FX Clear is ideal for producing a variety of special effects on all prepared interior surfaces such as plaster, plasterboard, cement and timber.

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply one coat of FX Max Superprep Undercoat as required, followed by FX Max Semi-Gloss, white or tinted.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer using an upward action.

Brush/Roller: When using a tinted FX Clear, apply with a soft, medium or long nap roller or with a 75 mm–100 mm brush. Then while wet, use a spatula, plastic bag or plastic card to create the desired finish. Further coats can be applied to vary special effects.

Note: Ensure each FX Clear coat is completely dry before proceeding to the next application.

Conventional Spray: Suitable for application using all standard spray equipment.

Approximate Spreading Rate: 6–10 square metres per litre, depending on application technique and surface roughness.

Approximate Film Thickness per coat: Wet: 150 Microns; **Dry:** 25 Microns.

Requires: 1 coat as a protective finish, 1 or more coats to achieve special effects.

Thinner: N/A.

Tinting: Refer to colour chart for tinting specifications.

Method: Brush, roller, special rollers, sponge, spatula, chamois or conventional spray equipment.

Drying Times (at 25 °C): Touch: 4 Hours; **Recoat:** 12 Hours.

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C. The temperature should not fall below 10 °C during the drying process.

Clean-up: Water. **Safety:** Dust Mask. **Gloss Level:** 20%–30% at a 60° viewing angle. Greater than 60 on glossy substrate.

Safety and Environmental Care

First Aid

Keep out of reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. If eyes or skin become irritated, flush / clean with water then seek medical attention. If swallowed DO NOT INDUCE VOMITING and seek medical attention.

Personal Protection

Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation. Wear appropriate safety breathing apparatus when sanding.

Asbestos cement sheeting

Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite, or other inert material. Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.



FX Australia® Product Information

FX Clear (Interior only)

IMPORTANT NOTES:

Always read the Product Information Sheet and label to ensure this product is appropriate for your project. If unsure contact FX Australia direct. Always test the product before commencing a project.

Ensure the entire process from preparation coat to finish coat incorporates all stages and only uses the recommended FX Products (the 'FX System'). DO NOT insert non-FX branded products into an FX System without the written approval of FX. Failure to follow FX recommendations or application steps may result in product failure and may void any warranty.

For any uncommon substrates, unusual angles or structures call FX direct to ensure the proposed FX product and system are appropriate.

The information in this Product Information Sheet is supplied in good faith. Other than as required under the Australian Consumer Law and any other relevant and applicable New South Wales and/or Australian Commonwealth legislation, FX provides no warranties or representations in supplying this product.

Date of issue: April 2023

