



## FX Australia® Product Information

### FX Maximus® (Interior & Exterior)

FX Australia recommends an experienced applicator for this product.

#### Product Description

FX Maximus® is a tough membrane coating producing a distinctive, highly textured Mediterranean finish. FX Maximus® is suited to both interior and exterior use. Different application methods will result in a range of surface effects, varying from refined to rustic. **This is a specialty product. The end-result may differ from the FX Standard or images on social media depending on applicator technique and expertise. Always test the product before commencing a project.**

#### Features

Water-based  
Flexible  
Excellent water resistance

#### Benefits

Ease of application  
Easy spreading  
Easy clean-up

#### Uses

FX Maximus® can be used on a wide variety of surfaces, including plaster, plasterboard, cement blocks, bare-faced brick and cement render.

#### Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply FX Max Solar Superprep Undercoat on unpainted surfaces.

**Note: Best results are achieved on smooth, well-prepared surfaces.**

#### Application

Stir contents thoroughly before and during use with a broad, flat stirrer using an upward action.

**Brush/Roller/Mitt:** Apply 1–2 coats with a brush, 22 mm–32 mm roller, or textured roller. Or, for a rustic or bagged effect, apply with a mitt.

**Conventional Spray:** Not recommended.

**Approximate Spreading Rate:** 1–2 square metres per litre, depending on application technique and surface roughness.

**Approximate Film Thickness per coat: Wet:** 500 Microns; **Dry:** 250 Microns.

**Requires:** 1–2 coats.

**Thinner:** Not required.

**Tinting:** Refer to colour chart for tinting specifications.

**Method:** Brush, roller, special rollers, mitt or sponge.

**Drying Times (at 25 °C): Touch:** 2 Hours; **Recoat:** 6 Hours.

**Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.**

**The temperature should not fall below 10 °C during the drying process.**

**Clean-up:** Water. **Safety:** Dust Mask. **Gloss Level:** NA

#### Safety and Environmental Care

##### First Aid

Keep out of reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. If eyes or skin become irritated, flush / clean with water then seek medical attention. If swallowed DO NOT INDUCE VOMITING and seek medical attention.

##### Personal Protection

Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation. Wear appropriate safety breathing apparatus when sanding.

**Asbestos cement sheeting:** Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

##### Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite, or other inert material. Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

##### Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

##### Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.



## FX Australia® Product Information

### *FX Maximus® (Interior & Exterior)*

FX Australia recommends an experienced applicator for this product.

#### Important Notes:

Always read the Product Information Sheet, Safety Data Sheet and label to ensure this product is appropriate for your project. Always test the product before commencing a project to check its suitability. If unsure, contact FX Australia direct.

Ensure the entire process from preparation coat to finish coat incorporates all stages and only uses the recommended FX Products (the 'FX System'). DO NOT insert non-FX branded products into an FX System without the written approval of FX. Failure to follow FX recommendations or application steps may result in product failure and may void any warranty.

For any uncommon substrates, unusual angles or structures call FX direct to ensure the proposed FX product and system are appropriate.

The information in this Product Information Sheet is supplied in good faith. Other than as required under the Australian Consumer Law and any other relevant and applicable New South Wales and/or Australian Commonwealth legislation, FX provides no warranties or representations in supplying this product.

**Date of Reissue: April 2023**

