



FX Australia® Product Information

FX Marmorino Smooth & Coarse (Interior & Exterior)

An experienced applicator is highly recommended for this product.

Product Description

FX Marmorino Smooth and Coarse are marble-based, render-like coatings that replicates the seasoned, elegant interiors and exteriors of Italy's grand villas. Different application methods and finishing techniques produce varying special effects; smooth and subtle or mottled and textured, flat finished or with a slight sheen. **This is a specialty product. The end-result may differ from the FX Standard or images on social media depending on applicator technique and expertise. Always test the product before commencing a project.**

Features

Water-based
Attractive finishes
Varying effects
Tintable

Benefits

Ease of application
Easy spreading
Easy clean-up

Uses

FX Marmorino Smooth and Coarse can be applied on all sealed surfaces such as plaster, plasterboard and rendered walls.

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply FX Stucco Undercoat as required. **On pre-painted (water-based) surfaces** apply one coat of FX Stucco Undercoat before applying FX Marmorino Smooth or Coarse.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer, using an upward action, or preferably use a power-driven mixing paddle.

Trowel: Requires 2-3 coats applied with a stainless-steel stucco trowel. Different sized trowels give different effects. Place a small amount of product onto the trowel and apply as evenly as possible. The trowel is held at an approximate 45-degree angle to the surface during application. Apply second coat using the same method after 6 hours drying time. To achieve a slight sheen, rub the trowel over the surface, using as for the application, while surface is still wet.

Or when dry, polish using a fine sanding block and then move trowel over the surface. Can also be left flat.

Note: On smooth surfaces, only two coats are required. Rough surfaces require further coats.

Note: Do not apply in direct sunlight.

Clear Coating: FX Wicked Wax® or FX Liquid Wax can be applied to seal finished surface – interior use only.

Approximate Spreading Rate: 4-6 square metres per 1.5KG, depending on application technique and surface roughness.

Approximate Film Thickness per coat: Not applicable – depends on application.

Requires: 2 coats minimum, more coats on rough surfaces.

Thinner: Not required.

Tinting: Refer to colour chart for tinting specifications.

Method: Stainless steel stucco trowel.

Drying Times (at 25 °C): Touch: 2 Hours; **Recoat:** 6-8 Hours.

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.

The temperature should not fall below 10 °C during the drying process.

Clean-up: Water. **Safety:** Dust Mask. **Gloss Level:** NA

Safety and Environmental Care

First Aid

Keep out of reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. If eyes or skin become irritated, flush / clean with water then seek medical attention. If swallowed DO NOT INDUCE VOMITING and seek medical attention.

Personal Protection

Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation. Wear appropriate safety breathing apparatus when sanding.

Asbestos cement sheeting

Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite, or other inert material. Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.



FX Australia® Product Information

FX Marmorino Smooth & Coarse (Interior & Exterior)

An experienced applicator is highly recommended for this product.

Important Notes:

Always read the Product Information Sheet and label to ensure this product is appropriate for your project. If unsure contact FX Australia direct. Always test the product before commencing a project.

FX Marmorino is porous. It is highly recommended a topcoat of FX Wicked Wax (INTERIOR ONLY) is applied as a protective coating to ensure the finish is durable.

Respect the drying times before applying the wax.

Ensure the entire process from preparation coat to finish coat incorporates all stages and only uses the recommended FX Products (the 'FX System'). DO NOT insert non-FX branded products into an FX System without the written approval of FX. Failure to follow FX recommendations or application steps may result in product failure and may void any warranty.

For any uncommon substrates, unusual angles or structures call FX direct to ensure the proposed FX product and system are appropriate.

The information in this Product Information Sheet is supplied in good faith. Other than as required under the Australian Consumer Law and any other relevant and applicable New South Wales and/or Australian Commonwealth legislation, FX provides no warranties or representations in supplying this product.

Date of Reissue: April 2023

