



## FX Australia® Product Information

### FX French Wash (Interior only)

#### Product Description

FX French Wash is a unique acrylic-based coating using modern technology to create a delicate, two-tone classic French Provincial look that's matt when dry. Various application methods can produce a range of effects, and the coating can also be used to create traditional marble effects. **This is a specialty product. The end-result may differ from the FX Standard or images on social media depending on applicator technique and expertise. Always test the product before commencing a project.**

#### Features

Water-based  
Attractive finish  
Smooth finish  
Tintable

#### Benefits

Ease of application  
Easy spreading  
Easy clean-up

#### Uses

FX French Wash produces many different special effects on all prepared interior surfaces such as plaster and plasterboard, and on bagged and rendered walls.

#### Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply Max Solar Superprep Undercoat as required. Follow with two coats of FX Max Easy Clean Low Sheen or FX Max Semi-Gloss, white or tinted. Apply FX French Wash when base paint is completely dry.

#### Application

Stir contents thoroughly before use with a broad, flat stirrer using an upward action.

**Brush/Roller:** Use a 75 mm or 100 mm brush or a short or long nap roller to apply the first coat. While still wet, use a rag rolling technique with a cheesecloth, sea sponge, or brush in a criss-cross motion to produce the desired effect. Several coats can be applied to achieve different finishes, ensure first coat is dry before proceeding to further applications.

**Note: Always keep a wet edge and work in a random, zigzag motion from top to bottom.**

**For a traditional marble effect,** brush on two different colours in a random zigzag pattern. Smear the two colours together using a cheesecloth; this is the marble base. Next, dip a feather into a different colour and draw the tip diagonally over the surface to form veins. Repeat feathering until satisfied. Simple, uncomplicated feathering is best. We suggest that novice applicators practice this technique before commencing a project. To protect, apply one coat of FX Super Matt Clear.

**Note: FX Scumble may be added to the paint to slow down drying time for large areas and during hot or humid weather conditions. Add no more than 10%.**

**Approximate Spreading Rate:** 16 square metres per litre, depending on application technique and surface roughness.

**Approximate Film Thickness per coat: Wet:** 45 Microns; **Dry:** 10 Microns.

**Requires:** 1 coat for a simple French Wash finish.

**Thinner:** Not usually required.

**Tinting:** Refer to colour chart for tinting specifications.

**Method:** Brush, roller, sponge, rag rolling, cheesecloth or feather.

**Drying Times (at 25 °C): Touch:** 2 Hours; **Recoat:** Not usually required.

**Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C. The temperature should not fall below 10 °C during the drying process.**

**Clean-up:** Water. **Safety:** Dust Mask. **Gloss level:** Less than 5% at a 60° viewing angle.

#### Safety and Environmental Care

##### First Aid

Keep out of reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. If eyes or skin become irritated, flush / clean with water then seek medical attention. If swallowed DO NOT INDUCE VOMITING and seek medical attention.

##### Personal Protection

Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation. Wear appropriate safety breathing apparatus when sanding.

##### Asbestos cement sheeting

Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.

##### Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite, or other inert material. Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

##### Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

##### Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.



## FX Australia® Product Information

### *FX French Wash* (Interior only)

#### Important Notes:

**Always read the Product Information Sheet and label to ensure this product is appropriate for your project. If unsure contact FX Australia direct. Always test the product before commencing a project.**

Ensure the entire process from preparation coat to finish coat incorporates all stages and only uses the recommended FX Products (the 'FX System'). DO NOT insert non-FX branded products into an FX System without the written approval of FX. Failure to follow FX recommendations or application steps may result in product failure and may void any warranty.

For any uncommon substrates, unusual angles or structures call FX direct to ensure the proposed FX product and system are appropriate.

**The information in this Product Information Sheet is supplied in good faith. Other than as required under the Australian Consumer Law and any other relevant and applicable New South Wales and/or Australian Commonwealth legislation, FX provides no warranties or representations in supplying this product.**

**Date of issue: April 2023**

