



FX Australia® Product Information

FX Vintage Crackle (Interior only)

Product Description

FX Vintage Crackle is a liquid medium, specifically formulated to reproduce the aged, weathered look that makes the old new again and the new deceptively old. Use it on feature walls, furniture, woodwork, picture frames, statuary – wherever you want the antique charm of a crackle finish to make a contemporary decorating statement. For perfect results, combine with the FX Max products recommended below. **Note:** FX Crackle Effect, used with FX Flexible or FX Easy Sanding Stucco, will create a 'cracked earth' effect, an unusual finish suited to many design and architectural projects. Contact FX Australia direct for further details.

This is a specialty product. The end-result may differ from the FX Standard or images on social media depending on applicator technique and expertise. Always test the product before commencing a project.

Features

Water-based
Attractive finish

Benefits

Ease of application
Easy spreading
Easy clean-up

Uses

FX Crackle Effect can be applied to any properly prepared interior surface, such as plaster, plasterboard, timber, concrete, cement and cement render. Different application techniques can produce a variety of exciting finishes.

Surface Preparation

All surfaces must be thoroughly cleaned and free of dirt, dust, grease, loose or flaking paint and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. Then apply one coat of FX Max Superprep Undercoat as required. Pre-painted surfaces in good condition may need only light sanding and removal of any dust particles before proceeding.

Application

Stir contents thoroughly before and during use with a broad, flat stirrer using an upward action. **For a finer crackle effect, add water, up to 10% maximum.**

Step 1, base colour coat

Brush/Roller: Apply one coat of FX Max Easy Clean Low Sheen or Semi-Gloss in your choice of colour. Use a 12 mm–20 mm nap roller or a 50 mm–75 mm brush. Allow up to 4-5 hours to dry before proceeding to Step 2.

Step 2, FX Vintage Crackle / crackle effect coat

Apply with a 12 mm–20 mm roller or with a 50 mm–75 mm brush. Ensure the product is applied evenly to a uniform gloss, leaving no uneven patches. If the surface is patchy, apply a second coat of FX Vintage Crackle after 3 hours drying time. After 4 hours, when the product is touch-dry, proceed to Step 3.

Step 3, finish colour coat

Apply one coat of FX Max Easy Clean Low Sheen or Semi-Gloss, in your choice of colour. Use a 12 mm–20 mm roller or with a 50 mm–75 mm brush. Crackle effect will start to appear in 25–30 minutes. Leave to dry for 12 hours minimum.

Note: You may leave Step 3 as the final effect or apply one coat of FX Super Matt Clear to protect the finish / surface.

Conventional Spray: Suitable for application using all standard spray equipment.

Approximate Spreading Rate: 6–10 square metres per litre, depending on application technique and surface roughness.

Approximate Film Thickness per coat: N/A

Requires: See Application Instructions above.

Thinner: N/A.

Tinting: N/A

Method: Brush, roller or conventional spray equipment.

Drying Times (at 25 °C): Touch: 4 Hours; **Recoat:** 12 Hours.

Note: Do not apply paint if the air temperature or substrate temperature is below 10 °C or above 35 °C.

The temperature should not fall below 10 °C during the drying process.

Clean-up: Water. **Safety:** Dust Mask. **Gloss Level:** N/A

Safety and Environmental Care

First Aid

Keep out of reach of children. Provide adequate ventilation. Avoid contact with skin and eyes. If eyes or skin become irritated, flush / clean with water then seek medical attention. If swallowed DO NOT INDUCE VOMITING and seek medical attention.

Personal Protection

Wear eye protection and dust mask when spraying, as splashes may cause eye irritation and inhalation of spray mist may cause respiratory irritation. Wear appropriate safety breathing apparatus when sanding.

Asbestos cement sheeting

Do not disturb, sand or scrub, and avoid any peripheral dust. If you do not have professional expertise in the handling/removal of asbestos sheeting, use a licensed asbestos removalist.

Refer to product labels, current FX Australia Safety Data Sheets or call FX Australia for detailed information.



FX Australia® Product Information

FX Vintage Crackle (Interior only)

Safety and Environmental Care (continued)

Clean-up

Slippery when spilled • Restrict access to area until clean-up is completed • When cleaning up spills, use personal protection equipment • Stop leak if safe to do so and contain spill with absorbent material such as sand, vermiculite, or other inert material. Prevent spill from entering waterways • Collect and dispose of spilled material according to local regulations • Wash away remnants with liberal amounts of cold water.

Storage

Store in a cool, dry, well-ventilated place out of direct sunlight • Store away from strong acids and moisture • Keep containers closed at all times and check regularly for spills.

Disposal

Refer to State/Territory Land Waste Management Authority: most authorities permit disposal at approved land waste sites.

Important Notes:

Always read the Product Information Sheet and label to ensure this product is appropriate for your project. If unsure contact FX Australia direct. Always test the product before commencing a project.

Ensure the entire process from preparation coat to finish coat incorporates all stages and only uses the recommended FX Products (the 'FX System'). DO NOT insert non-FX branded products into an FX System without the written approval of FX. Failure to follow FX recommendations or application steps may result in product failure and may void any warranty.

For any uncommon substrates, unusual angles or structures call FX direct to ensure the proposed FX product and system are appropriate.

The information in this Product Information Sheet is supplied in good faith. Other than as required under the Australian Consumer Law and any other relevant and applicable New South Wales and/or Australian Commonwealth legislation, FX provides no warranties or representations in supplying this product.

Date of Reissue: April 2023

